

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
12 August 2004 (12.08.2004)

PCT

(10) International Publication Number
WO 2004/068403 A2

BEST AVAILABLE COPY

(51) International Patent Classification⁷:

G06T

(74) Agents: PIRIO, Maurice, J. et al.; Perkins Coie LLP,
Patent - SEA, P.O. BOX 1247, Seattle, WA 98111-1247
(US).

(21) International Application Number:

PCT/US2004/001053

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 14 January 2004 (14.01.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

60/440,977	17 January 2003 (17.01.2003)	US
60/440,976	17 January 2003 (17.01.2003)	US
60/440,983	17 January 2003 (17.01.2003)	US
10/726,334	1 December 2003 (01.12.2003)	US

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): THE INSITU GROUP [US/US]; 154-D East Bingen Point Way, Bingen, WA 98605 (US).

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): VONFLOTOW, Andreas, H. [US/US]; 1750 Country Club Road, Hood River, OR 97031 (US). MERCADAL, Mathieu [US/US]; 1751 Markham Road, Hood River, OR 97031 (US). MCGEER, Brian, T. [US/US]; 11482 Cook Underwood Road, Underwood, WA 98651 (US).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: COOPERATIVE NESTING OF MECHANICAL AND ELECTRONIC STABILIZATION FOR AN AIRBORNE CAMERA SYSTEM

(57) Abstract: A method and system for stabilizing images being taken by a video camera using electromechanical stabilization. The stabilization system performs inter-frame stabilization based on the velocity of a vehicle on which the video camera is mounted and the pan rate of a line-of-sight controller of the video camera. The inter-frame stabilization is performed by a software component by moving a display area (or viewport) within a larger image area. The stabilization system converts an inter-frame stabilization adjustment into a pan rate adjustment so that the line-of-sight controller will keep the desired object within the image area of the camera.

WO 2004/068403 A2

COOPERATIVE NESTING OF MECHANICAL AND ELECTRONIC STABILIZATION FOR AN AIRBORNE CAMERA SYSTEM

TECHNICAL FIELD

[0001] The described technology stabilizes an image stream created by an airborne video camera.

BACKGROUND

[0002] If not stabilized, the image streams created by airborne video cameras can be practically unusable for human observation because frame-to-frame image jitter is excessive. This image jitter typically is caused by small, fast pointing errors superposed upon larger-amplitude, slower pointing errors.

[0003] It is possible to reduce this image jitter to acceptable levels with refined mechanical stabilization techniques, stabilizing the line of sight of the image so that image jitter amplitude is less than an acceptable limit. Such an approach can deliver high-quality image streams from all types of cameras (video or film) but leads to large, heavy mechanical systems for support of the airborne camera. Such systems are the subject of U.S. Patent Nos. 5,897,223; 3,638,502; 4,989,466; 4,643,539; and 5,184,521. An approach relying purely upon mechanical stabilization leads to heavy and complex mechanical systems. Usually, multiple nested mechanical stages of stabilization are required, with each stage reducing the image jitter further, purely by reduction in jitter of the line of sight.

[0004] It would be desirable to have a technique to reduce jitter and avoid the need to have such large, heavy, and expensive mechanical systems.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] Figure 1 is a block diagram that illustrates the bases of the stabilization system in one embodiment.

[0006] Figure 2 is a block diagram that illustrates nesting of the two types of image stabilization in one embodiment.

- [0007] Figure 3 is a block diagram that illustrates a coupling from the camera pointing system to the stabilization system in one embodiment.
- [0008] Figure 4A is a graph that illustrates a typical error budget for the cooperative efforts of the various levels of image stabilization employed by the stabilization system in one embodiment.
- [0009] Figure 4B is a block diagram illustrating two types of electronic stabilization systems.
- [0010] Figure 5 is a diagram illustrating the reference frames used in the electromechanical stabilization system.
- [0011] Figure 6 illustrates the pixel offsets on an object from one frame to the next in one embodiment.
- [0012] Figure 7 is a flow diagram illustrating the processing of the stabilization system in one embodiment.
- [0013] Figure 8 is a flow diagram illustrating the processing of the analyze pixel offsets for velocity component in one embodiment.
- [0014] Figure 9 is a flow diagram illustrating the processing of the adjust pixel offsets for aircraft velocity in one embodiment.
- [0015] Figure 10 is a flow diagram illustrating the processing of the adjust pixel offsets for camera rotation component in one embodiment.
- [0016] Figure 11 is a flow diagram illustrating the processing of the adjust for image analysis by the electromechanical stabilization in one embodiment.

DETAILED DESCRIPTION

- [0017] A method and system for stabilizing images being taken by a video camera using electromechanical stabilization is provided. In one embodiment, the stabilization system performs inter-frame stabilization based on the velocity of a vehicle on which the video camera is mounted and the pan rate of a line-of-sight controller of the video camera. The inter-frame stabilization is performed by a software component by moving a display area (or viewport) within a larger image area. The inter-frame stabilization removes small-amplitude jitter while accounting for vehicle velocity and orientation, pan rate and orientation of the line-of-sight controller, distance to

an object within the image, and field of view of the camera. The stabilization system converts an inter-frame stabilization adjustment into a pan rate adjustment so the line-of-sight controller will keep the desired object within the image area of the camera. In this way, the stabilization system uses an electronic stabilization to remove small-amplitude jitters and feeds those adjustments to a mechanical stabilization to account for large-amplitude jitter.

[0018] In one embodiment, the stabilization system comprises a video camera controlled by a gimbal-based, line-of-sight controller that is mounted on an aircraft. While the aircraft is flying, the video camera feeds images to the software component that provides the inter-frame stabilization based on the scan and tilt rate (i.e., pan rate) of the line-of-sight controller. The software component removes small-amplitude jitter while factoring in the scan and tilt rate of the line-of-sight controller. The software component receives images from the camera that are larger than the display area. The software component moves the display area around within the larger image to remove the small-amplitude jitter. The software component then calculates a scan and tilt rate adjustment for the line-of-sight controller. The software component then provides the adjustment to the line-of-site controller so it can keep the video camera at the desired line of sight.

[0019] The stabilization system nests mechanical stabilization and electronic stabilization loops to exploit modern capabilities in electronics and image processing. Because not all of the stabilization is achieved mechanically, a simpler, cheaper, smaller, lighter, and lower-power mechanical gimbal system may be used.

[0020] The stabilization system uses an electronic image stabilization to augment mechanical line-of-sight stabilization to achieve full frame-to-frame stabilization of the image flow. The mechanical system is used for the large-amplitude, slow line-of-sight corrections required, while electronic stabilization is used for the small-amplitude, faster corrections not handled by the mechanical system. These stabilization loops are nested to take advantage of the characteristics of both types of stabilization. The

stabilization system can implement various levels of interaction between these stabilization methods.

Inner-to-Outer Nulling

[0021] The fastest, smallest-amplitude stabilization is implemented electronically by "sliding" successive frames in the image stream on the display screen or on the focal plane array within the camera. This type of stabilization accounts for small amplitudes, typically a small fraction of the frame. The stabilization system provides the image correction implemented by this electronic stabilization to the mechanical pointing system (i.e., the line-of-sight controller) so that the mechanical pointing system can implement movements to cause the long-term average electronic image correction to tend toward zero. If such corrections are not implemented by the mechanical pointing system, then the displayed image might slowly drift and exceed the limits of practical correction of the electronic stabilization.

Outer-to-Inner Coupling

[0022] A user may want the image to "flow" across the screen, as for example, when the camera is panned while images are being gathered. An electronic stabilization system may misinterpret such image flow as unwanted jitter and will attempt to correct for it. Such misinterpretation would lead to momentarily stabilized images with sudden "steps" required when the electronic correction reaches its practical limit. The stabilization system can prevent such sudden steps if provided with image flow from the command system of the mechanical pointing system. Thus, the stabilization system can be used to enable smooth electronic image stabilization, even when the camera is being panned across a scene and the image flows across the display screen.

[0023] Figure 1 is a block diagram that illustrates the bases of the stabilization system in one embodiment. Large-amplitude stabilization of camera line of sight is implemented with a motor-driven gimbal system 101 for controlling a camera 105. Small-amplitude stabilization of inter-frame motion is accomplished by electronic stabilization techniques implemented via an image processor 102. These electronic techniques shift the displayed

image on a display screen 103 electronically by an adjustment and feed the adjustment to a gimbal controller 104. The image processor 102 may include a central processing unit, memory, input devices (e.g., keyboard and pointing devices), output devices (e.g., display devices), and storage devices (e.g., disk drives). The memory and storage devices are computer-readable media that may contain instructions that implement the electronic stabilization of the video stream provided by the camera 105. In addition, data structures and message structures (e.g., gimbal controller command and gimbal scan and tilt rate) may be stored or transmitted via a data transmission medium, such as a signal on a communications link.

[0024] Figure 2 is a block diagram that illustrates the adjustment of the pan rate of the camera based on the inter-frame adjustment in one embodiment. The adjustment to the mechanical pointing system reduces any accumulating electronic image re-registration by mechanically re-pointing the camera. This allows the stabilization system to stabilize the image stream with a minimal loss of image size.

[0025] Figure 3 is a block diagram that illustrates the adjustment of the inter-frame stabilization based on the pan rate of the camera in one embodiment. This adjustment enables the stabilization system to stabilize successive images not simply in the display frame but rather to stabilize only unwanted motion between successive images. Thus, when the camera line of sight is intentionally panning the scene, the desired image flow is not suppressed by the stabilization system. Rather, the stabilization system suppresses only deviations from this desired image flow.

[0026] Figure 4A is a graph that illustrates a typical error budget for the cooperative efforts of the various levels of image stabilization employed by the stabilization system in one embodiment. Low-speed, large-amplitude stabilization is implemented by the mechanical gimbal system, while high-speed, small-amplitude stabilization is implemented by the electronic stabilization system.

[0027] Figure 4B is a block diagram illustrating two types of electronic stabilization systems. Gyro-to-image electronic stabilization 401 measures

mechanical motion of the camera body and implements image re-registration to compensate for this mechanical motion. Such electronic image stabilization is implemented in some hand-held "camcorder" video cameras sold in retail stores by Sony, Panasonic, and others. Gyro-to-image electronic stabilization is most practically implemented in airborne hardware and software within an airborne camera system. Frame-to-frame electronic image stabilization 402 employs image recognition techniques to re-register every frame prior to its display in a succession of image frames. Frame-to-frame stabilization attempts to minimize unwanted shift of successive frames on the display screen.

[0028] Figure 5 is a diagram illustrating the reference frames used in the stabilization system in one embodiment. The reference frame of the earth is represented by north N, east E, and down D coordinates. The position of an aircraft, which may be provided by an altimeter and a GPS system, is in the earth reference frame. The reference frame of the body of the aircraft is represented by heading B1, pitch B2, and roll B3 coordinates that may be provided by the aircraft's gyros. The reference frame of the camera is represented by a line of sight C1, tilt C2, and scan C3 coordinates. In one embodiment, the camera is controlled by an inertial stabilization system that controls the gimbal motors to control the orientation of the C1, C2, and C3 camera axes. The electromechanical stabilization system receives camera scan and tilt rate information from the camera rate gyros and adjusts these rates to further account for frame-to-frame jitter information and image recognition, which are provided by the electronic stabilization.

[0029] The stabilization system inputs the images generated by the camera, the velocity of the aircraft in the earth reference frame V_{aircraft}^B , the camera scan rate and tilt rate, the orientations of the aircraft and the camera, and the distance to an object in the images. The stabilization system analyzes consecutive frames and determines the optimal translation of one frame to make it best coincide with the preceding frame. The stabilization system may use conventional pattern recognition techniques to locate the object within the image. The stabilization system provides an offset in pixels to best

superimpose one frame onto the next frame. The pixel offsets may be represented as the number of pixels horizontally (also referred to as the scan direction) and the number of pixels vertically (also referred to as the tilt direction) on the display. In one embodiment, the stabilization system has an image buffer in memory that is larger than the displayed image. When the stabilization system detects variations in the position of an object resulting from jitter, it can offset the displayed image by the calculated scan and tilt offset, providing a frame that best superimposes with the previous displayed frame, thus effectively removing the jitter.

[0030] Figure 6 illustrates the pixel offsets on an object from one frame to the next in one embodiment. The memory buffer stores the image received from the camera using 2000 by 2000 pixels. However, only 1800 by 1800 pixels are displayed on the display. Thus, the image can be adjusted by 100 pixels in the negative and positive scan and tilt directions to account for jitter, assuming the last frame was centered in the memory buffer. In this example, a car is at position (1000, 1000) in the first frame, and the upper left corner of the display corresponds to position (101, 101). In a subsequent frame, the car is now at position (1010, 1020). Thus, the stabilization system can display position (111, 121) as the upper left corner of the display to place the car at the same position on the display from one frame to the next frame.

[0031] Since the camera may be panning a scene and the aircraft platform may be moving relative to the scene, a portion of the pixel offsets calculated by the stabilization system may be a result of this desired movement. In such a case, the stabilization system is provided with aircraft velocity and orientation, camera line of sight and orientation, and camera scan and tilt rate to estimate and factor out this desired movement before adjusting the image. The stabilization system calculates the sum of the pixel offsets resulting from the aircraft velocity and orientation, and the camera orientation and angular rate. The stabilization system then subtracts this sum from the pixel offsets calculated from the image analysis to give the pixel offsets attributable to the jitter.

[0032] Because the number of offset pixels is limited, the electromechanical stabilization loop keeps the desired image in the center of the camera. To do so, the stabilization system uses the pixel offsets to re-center the gimbal angles of the camera. The stabilization system converts the pixel offsets to corresponding scan and tilt error. The stabilization system also calculates scan and tilt rates. It then adjusts the scan and tilt rate of the camera to track an object or prevent an overflow of the pixel offset in the stabilization system.

[0033] The stabilization system uses transformation matrices to represent the current orientation of the body of the aircraft relative to the earth reference frame and the current orientation of the camera to the body reference frame. The camera reference frame relative to the body of the plane reference frame is represented by a transformation matrix C_{CB} for transforming a vector from the body reference frame to the camera reference frame. C_{CB} is a 3-by-3 matrix whose columns are orthogonal and normalized, also referred to as a matrix of direction cosines. The following equation represents the conversion of a position in the body reference frame to the camera reference frame:

$$R^C = C_{CB} R^B \quad (1)$$

where R^B represents the position in the body reference frame and R^C represents the position in the camera reference frame. An example C_{CB} is

$$\begin{matrix} 2^{-1/2} & -2^{-1/2} & 0 \\ 2^{-1/2} & 2^{-1/2} & 0 \\ 0 & 0 & 1 \end{matrix} \quad (2)$$

The matrix C_{CB} is set based on the angles of the gimbal relative to the body. Thus, this matrix represents the current gimbal angles. A matrix C_{BE} is for transforming from the earth reference frame to the body reference frame. Thus, the matrix C_{BE} represents the heading, pitch, and roll of the aircraft as measured by the gyro of the aircraft.

[0034] Figure 7 is a flow diagram illustrating the processing of the stabilization system in one embodiment. The stabilization system calculates an initial image adjustment based on analysis of the image. The stabilization system then adjusts the initial adjustment based on velocity and orientation of

the aircraft and the scan and tilt rate of the camera. In block 701, the system invokes a component to analyze the image and calculate image pixel offsets. The invoked component provides the scan and tilt pixel offsets. The component may use standard object recognition techniques to recognize an object in successive frames and set the initial adjustment based on the difference in locations of the object. In block 702, the system invokes the adjust pixel offset component, which determines the velocity pixel offsets that are attributable to the desired aircraft velocity, the rotation of the camera, and the orientations of the aircraft and the camera. In blocks 703-704, the system calculates pixel offsets due to unwanted image jitter by subtracting the velocity pixel offsets and desired camera rotation pixel offsets from the image pixel offsets. In block 705, the stabilization system displays the stabilized image by selecting the portion of the screen that begins at the newly calculated offsets. In block 706, the system invokes the adjust for image analysis component providing the pixel offsets to calculate a change in the scan and tilt rate of the camera to help ensure that the image correction will not exceed the maximum number of allowable pixels. In block 707, the system adjusts the scan and tilt rate of the camera. The system may be invoked to process every frame or only a subset of the frames (e.g., every 10 frames).

[0035] Figure 8 is a flow diagram illustrating the processing of the analyze pixel offsets for velocity component in one embodiment. The component is provided with the velocity of the aircraft V_{aircraft}^B in the earth reference frame, the orientation of the aircraft C_{BB} , and the orientation of the camera C_{CB} . In block 801, the component invokes the adjust pixel offsets for aircraft velocity component to calculate the pixel offsets attributable to the velocity of the aircraft. In block 802, the component invokes the adjust pixel offsets for camera rotation component to calculate the pixel offsets attributable to the rotation of the camera. In blocks 803-804, the component combines the pixel offsets for the scan and tilt directions.

[0036] Figure 9 is a flow diagram illustrating the processing of the adjust pixel offsets for aircraft velocity in one embodiment. In block 901, the component

calculates a transformation matrix for transforming from the earth reference frame to the camera reference frame as follows:

$$C_{CE} = C_{CB} C_{BE} \quad (3)$$

In block 902, the component calculates the line of sight of the camera in the earth reference frame as

$$L^E = C_{CE}^T (1, 0, 0)^T \quad (4)$$

where L^E is the line of sight of the camera in the earth reference frame and where the superscript T represents the transpose of the matrix or vector. In block 903, the component retrieves the distance or range K to the object at the center of the camera. The range may be provided by a range finder or by calculating the distance using the altitude of the target. For example, if the object is at sea level, then the distance can be calculated based on the altitude of the aircraft and the angle of the line of sight. In block 904, the component transforms the velocity of the aircraft to the camera reference frame as

$$V_{aircraft}^C = C_{CE} * V_{aircraft}^E \quad (5)$$

In block 905, the component normalizes the velocity of the aircraft as

$$\tilde{V}_{aircraft}^C = V_{aircraft}^C / K \quad (6)$$

where $\tilde{V}_{aircraft}^C$ is the normalized velocity of the aircraft in radians per hour. For example, if the velocity of the aircraft in the scan direction is 100km/hr and the distance to the object is 1km, then the normalized velocity is 100rad/hr, which means the aircraft moves in the scan direction 100 times the distance to the object in one hour. In block 906, the component calculates the difference in scan units as

$$\Delta S^C = \tilde{V}_{aircraft}^C (S) * \Delta T \quad (7)$$

where ΔT is the frame refresh period. For example, when the normalized velocity is 100rad/hr and the refresh rate is 15 times per second, then the change in scan units is:

$$\frac{100rad}{hr} * \frac{1hr}{3600sec} * \frac{1sec}{15} = \frac{1}{540} rad = .11degrees \quad (8)$$

In block 907, the component calculates the aircraft pixel offset in the scan direction by converting the difference in scan units to the corresponding pixel offset factoring in the field of view (or zoom) of the camera. The component calculates the pixel offset as

$$APO(S) = \Delta S^C * P/Z \quad (9)$$

where $APO(S)$ is the pixel offset in the scan direction, Z is the zoom factor, and P is the pixel density. For example, if the scan units are $1/540rad$ and there are 2000 pixels in the scan direction with a field of view of $.93rad$ (1km field of view at 1km distance), the pixel offset is

$$\frac{1rad}{540} * \frac{2000pixels}{.93rad} = 4pixels \quad (10)$$

In blocks 908-909, the component calculates the pixel offset in the tilt direction in a similar manner.

[0037] Figure 10 is a flow diagram illustrating the processing of the adjust pixel offsets for the camera rotation component in one embodiment. The component receives the instantaneous camera scan and tilt rates from the gimbal controller. Alternatively, the component can calculate them based on the orientations of the aircraft and the camera. In block 1001, the component calculates the difference in scan units as

$$\Delta S^C = IS * \Delta T \quad (11)$$

where IS is the instantaneous scan rate of the camera measured by a rate gyro. In block 1002, the component calculates the difference in tilt units as

$$\Delta T^C = IT * \Delta T \quad (12)$$

where IT is the instantaneous tilt rate of the camera measured by a rate gyro. In block 1003, the component calculates the camera pixel offset in the scan direction by converting the difference in scan units to the corresponding pixel offset, factoring in the field of view (or zoom) of the camera. In block 1004,

the component calculates the pixel offset in the tilt direction in a similar manner.

[0038] Figure 11 is a flow diagram illustrating the processing of the adjust for image analysis by the stabilization in one embodiment. The component is passed the pixel offsets corresponding to the adjustments made by the stabilization system. In blocks 1101-1102, the component converts the pixel offsets to corresponding scan angle in radians and tilt angle in radians, factoring in the field of view of the camera. In blocks 1103-1104, the component calculates the angle error resulting from the pixel offsets as

$$AE(S) = \Delta S^C * K \quad (13)$$

$$AE(T) = \Delta T^C * K \quad (14)$$

where AE is the angle error and K is the distance to the center of the image. In blocks 1105-1106, the component calculates the adjustments for the angle errors as

$$A(S) = (W/\Delta T) * AE(S) \quad (15)$$

$$A(T) = (W/\Delta T) * AE(T) \quad (16)$$

where A(S) is the adjustment for the scan rate in radians per second and W is a weighting factor that controls the bandwidth of the feedback loop. The weighting factor controls the speed at which adjustments can be made to the scan and tilt rates. The stabilization system compares the adjustment to the scan rate of the camera provided by the gyro and uses the difference in rate to control the velocity of the gimbal motors.

[0039] All patents and articles cited herein are hereby incorporated by reference in their entirety and relied upon. Further details of methods of operating airborne cameras in accordance with other embodiments of the invention are described in U.S. Patent Application No. 60/440,983, filed on January 17, 2003, and entitled, "Compensation for Overflight Velocity When Stabilizing an Airborne Camera," and U.S. Patent Application No. 60/440,977, filed on January 17, 2003, and entitled, "Method and Apparatus

for Stabilizing Payload, Including Airborne Cameras," which are hereby incorporated by reference.

[0040] One skilled in the art will appreciate that although specific embodiments of the stabilization system have been described herein for purposes of illustration, various modifications may be made without deviating from the spirit and scope of the invention. For example, the principles of the stabilization system may be used on a transport mechanism other than an airplane, such as a satellite, a rocket, a missile, a train, an automobile, and so on. In addition, the camera may even be stationary or not traveling relative to an object in the video. Accordingly, the invention is not limited except by the appended claims.

CLAIMS

- [c1] 1. A method for stabilizing an image of an object being taken from a video camera, the video camera being moved by a transport mechanism and being controlled by a line-of-sight controller, the method comprising:
- receiving a plurality of images of the object; and
 - for each of the plurality of received images,
 - receiving a velocity and orientation of the transport mechanism;
 - receiving an orientation of the camera relative to the transport mechanism;
 - receiving a scan and tilt rate of the camera;
 - receiving a distance from the camera to the object;
 - calculating an inter-frame stabilization adjustment based on the velocity and orientation of the transport mechanism, the orientation of the camera, the scan and tilt rate of the camera, and distance to the object;
 - calculating a line-of-sight adjustment for the line-of-sight controller based on the inter-frame stabilization; and
 - controlling the line-of-sight controller in accordance with the calculated line-of-sight adjustment.
- [c2] 2. The method of claim 1 wherein the transport mechanism is an airborne vehicle.
- [c3] 3. The method of claim 1 wherein the line of sight of the camera is derived from the line-of-sight controller.
- [c4] 4. The method of claim 1 including adjusting the display of the images based on the inter-frame stabilization adjustment.

- [c5] 5. The method of claim 4 wherein the received images are larger than the displayed images and the adjusting of the display of the images moves an area of a displayed image within the received image.
- [c6] 6. The method of claim 4 wherein the inter-frame stabilization adjustment specifies the number of pixels in scan and tilt directions.
- [c7] 7. The method of claim 1 wherein the controlling of the line-of-sight controller specifies rate of scan and tilt movement.
- [c8] 8. The method of claim 1 wherein the distance to the object is provided by a range finder.
- [c9] 9. The method of claim 1 wherein the distance to the object is calculated based on the line of sight of the camera and the difference in altitude of the object and the camera.
- [c10] 10. The method of claim 1 wherein the velocity of the transport mechanism is relative to the object.
- [c11] 11. The method of claim 1 wherein the velocity of the transport mechanism is relative to an earth frame of reference.
- [c12] 12. The method of claim 1 wherein the calculated inter-frame stabilization adjustment factors in field of view of the display.
- [c13] 13. A method for stabilizing an image of an object being taken from a video camera, the video camera being moved by a transport mechanism and being controlled by a line-of-sight controller, the method comprising:
 determining a difference in the location of the object within the image
 from one frame to the next frame;

calculating an inter-frame stabilization adjustment based on the determined difference;
calculating a line-of-sight adjustment for the line-of-sight controller based on the inter-frame stabilization; and
controlling the line-of-sight controller in accordance with the calculated line-of-sight adjustment.

[c14] 14. The method of claim 13 wherein the determining of the difference includes analyzing scan and tilt rate of the line-of-sight controller.

[c15] 15. The method of claim 13 wherein the determining of the difference includes analyzing velocity of the transport mechanism.

[c16] 16. The method of claim 13 wherein the determining of the difference includes analyzing line of sight of the camera.

[c17] 17. The method of claim 13 wherein the determining of the difference includes analyzing orientation of the camera and the transport mechanism.

[c18] 18. The method of claim 13 wherein the determining of the difference includes recognizing the object within the images.

[c19] 19. The method of claim 13 wherein the calculated line-of-sight adjustment specifies a scan and tilt rate for the line-of-sight controller.

[c20] 20. An apparatus for stabilizing imagery from an airborne video camera, comprising:

a mechanical line-of-sight controller for controlling line of sight of the video camera at a specified line-of-sight adjustment rate; and
an electronic stabilization component that provides frame-to-frame image stabilization based on the specified line-of-sight

adjustment rate and that provides to the mechanical line-of-sight controller a new line-of-sight adjustment rate derived from an amount of frame-to-frame image stabilization.

- [c21] 21. The apparatus of claim 20 wherein the amount of frame-to-frame image stabilization is additionally based on velocity and orientation of an airborne transport vehicle, orientation of the camera relative to the airborne transport vehicle, and distance from the camera to an object within the image.
- [c22] 22. The apparatus of claim 20 wherein the line-of-sight adjustment rate includes a scan rate and a tilt rate.
- [c23] 23. The apparatus of claim 20 wherein an image received from the video camera is larger than a displayed image and the electronic stabilization component provides frame-to-frame image stabilization by adjusting the location of the displayed image within a received image.
- [c24] 24. The apparatus of claim 20 wherein the specified line-of-sight adjustment rate includes a user-specified image flow.
- [c25] 25. The apparatus of claim 20 wherein the mechanical line-of-sight controller is a motorized gimbal system.
- [c26] 26. The apparatus of claim 20 wherein the frame-to-frame adjustment keeps an object of the images at the same location when displayed.
- [c27] 27. An apparatus for stabilizing imagery from an airborne video camera, comprising:
a mechanical line-of-sight controller for controlling line of sight of the video camera at a specified line-of-sight adjustment rate; and

an electronic stabilization component that provides frame-to-frame image stabilization based on location of an object within the images and that provides to the mechanical line-of-sight controller a new line-of-sight adjustment rate derived from an amount of frame-to-frame image stabilization.

[c28] 28. The apparatus of claim 27 wherein an amount of frame-to-frame image stabilization is additionally based on velocity and orientation of an airborne transport vehicle, orientation of the camera relative to the airborne transport vehicle, and distance from the camera to the object within the image.

[c29] 29. The apparatus of claim 27 wherein an amount of frame-to-frame image stabilization is additional based on the specified line-of-sight adjustment rate.

[c30] 30. The apparatus of claim 27 wherein the line-of-sight adjustment rate includes a scan rate and a tilt rate.


[c31] 31. The apparatus of claim 27 wherein an image received from the video camera is larger than a displayed image and the electronic stabilization component provides frame-to-frame image stabilization by adjusting the location of the displayed image within a received image.


[c32] 32. The apparatus of claim 27 wherein the specified line-of-sight adjustment rate includes a user-specified image flow.


[c33] 33. The apparatus of claim 27 wherein the mechanical line-of-sight controller is a motorized gimbal system.


[c34] 34. The apparatus of claim 27 wherein the frame-to-frame adjustment keeps the object of the images at the same location when displayed.


- [c35] 35. A method for stabilizing images being taken from a video camera mounted on a moving vehicle, the camera having a line of sight being controlled by a line-of-sight controller, the method comprising:
- calculating inter-frame stabilization adjustments to account for velocity of the vehicle;
 - displaying the images in accordance with the calculated inter-frame stabilization adjustments;
 - calculating line-of-sight adjustments for the line-of-sight controller based on the inter-frame stabilization adjustments; and
 - controlling the line-of-sight controller in accordance with the calculated line-of-sight adjustments.
- [c36] 36. The method of claim 35 wherein the calculating of the inter-frame stabilization adjustments factors in scan and tilt rate of the line-of-sight controller.
- [c37] 37. The method of claim 35 wherein the calculating of the inter-frame stabilization adjustments factors in line of sight of the camera.
- [c38] 38. The method of claim 35 wherein the calculating of the inter-frame stabilization adjustments factors in orientation of the camera and the vehicle.
- [c39] 39. The method of claim 35 wherein the calculating of the inter-frame stabilization adjustments includes recognizing an object within the images.
- [c40] 40. The method of claim 35 wherein the calculated line-of-sight adjustment specifies a scan and tilt rate for the line-of-sight controller.

**FIG. 1**


**FIG. 2**


**FIG. 3**


**FIG. 4A**


Electronic Stabilization from Measured Camera Motion**Electronic Stabilization by Image Analysis**


402


**FIG. 4B**


**FIG. 5**


**FIG. 6**

**FIG. 7**

**FIG. 8**

**FIG. 9**

**FIG. 10**

**FIG. 11**

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.